

BDF Cling-Lube

PRODUKTBESCHREIBUNG:

JAX BDF Cling-Lube wurde zusammen mit Ingenieuren namhafter Schlachtbetrieben für Anwendungen über Kopf entwickelt und getestet.

Durch die spezielle Additivkombination haftet JAX BDF Cling Lube extrem an und ermöglicht unter extremen Druck und auch in feuchten Umgebungen einen hervorragenden Verschleißschutz.

Die schäumende Konsistenz bildet einen klebrigen, tropffreien Schmierfilm. JAX BDF Cling-Lube eignet sich durch die Vielzahl der Anwendungsmöglichkeiten als Problemlöser.

ANWENDUNGEN:

- Förderketten und Förderbänder
- Deckenhängebahnen
- Feuchte Umgebungen
- Extremer Druck
- Schwer Erreichbare Stellen

TECHNISCHE DATEN:

Treibmittel:	Propan und Butan
Flammpunkt:	352 ° F (178 ° C) Konzentrat, typisch -94 ° F (-70 ° C) Treibmittel, typisch
Sprühbild:	Schaum
Struktur:	Dick, Klebrig
Aussehen:	Helle, gelbe Farbe
Konsistenz:	Schwer

SPÜHDOSE:

11 Oz Nettogewicht Aerosoldosen (12 / case) - Teil # JAX214





NSF International / Nonfood Compounds Registration Program

October 03, 2002

Pressure-Lube, Inc. JAX
Attn: Patty Riek
W134 N5373 Campbell Drive
Menomonee Falls, WI 53051

RE JAX BDF CLING-LUBE (AEROSOL)
Category Code: H1
NSF Registration No. 127730

Dear Patty Riek:

NSF has processed the application for Registration of **JAX BDF CLING-LUBE (AEROSOL)** to the *NSF Registration Guidelines for Proprietary Substances and Nonfood Compounds (2002)*, which are available at www.nsf.org/usda. The NSF Nonfood Compounds Registration Program is a continuation of the USDA product approval and listing program, which is based on meeting regulatory requirements including FDA 21 CFR for appropriate use, ingredient and labeling.

This product is acceptable as a lubricant with incidental food contact (H1) for use in and around food processing areas. Such compounds may be used on food processing equipment as a protective anti-rust film, as a release agent on gaskets or seals of tank closures, and as a lubricant for machine parts and equipment in locations in which there is a potential exposure of the lubricated part to food. The amount used should be the minimum required to accomplish the desired technical effect on the equipment. If used as an anti-rust film, the compound must be removed from the equipment surface by washing or wiping, as required to leave the surface effectively free of any substance which could be transferred to food being processed.

NSF Registration of this product is current when the NSF Registration Number, Category Code, and Registration Mark appear on the NSF-approved product label, and the registered product name is included in the current NSF White Book Listing of Nonfood Compounds at the NSF website (<http://www.nsf.org/usda>). The NSF Registration Mark can be downloaded from the NSF website, at http://www.nsf.org/mark/download_marks.html.

NSF Listing of all registered Nonfood compounds by NSF International is not an endorsement of those compounds, or of any performance or efficacy claims made by the manufacturer.

Registration status may be verified at any time via the NSF web site, at <http://www.nsf.org/usda>. Changes in formulation or label, without the prior written consent of NSF, will void registration, and will supersede the on-line listing.

Sincerely,

Carmen Grindatti
NSF Nonfood Compounds Registration and listing program

Distributed By:

PRESSURE-LUBE
America's Finest Lubricants